

# Stratasys UV800






The UV800 oven & hot box for the complete Stratasys Neo® 3D printing solution.

The UV800 has been developed so that parts printed on the Neo can undergo a final post-cure process, optimizing and improving strength and performance of each part.

Designed with high intensity UV lamps and a turntable, the UV800 is controlled via PLC with HMI touchscreen and has pre-programmed post-curing cycles for ease of use.

The UV800 also features a heated resin store, so top up resin is maintained at the correct vat temperature.

## Specifications

Electrical Requirements	Rated Voltage	VAC	220 ~ 240
		Hz	50/60
	Peak Power	W	1450
	Peak Current	A	6.5
	Typical Power	W	950
Environment Requirements	Temperature Range	°C	17 ~ 25
		°F	62 ~ 77
	Heat Dissipation	W	950
Btu/h		3250	
Weight & Dimensions	Dimensions (W x D x H)	mm	1250 x 1250 x 1896
		in	49.2 x 49.2 x 74.7
	Weight	kg	300
		lb	661
Regulatory Conformity		    	

### USA - Headquarters

7665 Commerce Way  
Eden Prairie, MN 55344, USA  
+1 952 937 3000

### EMEA

Airport Boulevard B 120  
77836 Rheinmünster, Germany  
+49 7229 7772 0



GET IN TOUCH.

[www.stratasys.com/contact-us/locations](http://www.stratasys.com/contact-us/locations)

### ISRAEL - Headquarters

1 Holtzman St., Science Park  
PO Box 2496  
Rehovot 76124, Israel  
+972 74 745 4000

### SOUTH ASIA

1F A3, Ninghui Plaza  
No.718 Lingshi Road  
Shanghai, China  
+86 21 3319 6000

[stratasys.com](http://stratasys.com)

ISO 9001:2015 Certified

